

**DESCRIPTION**


TRAVEL : 90° ±5° AT BOTH ENDS.  
 RATIO : 52 : 1  
 TURNS TO CLOSE : 13  
 WEIGHT : 47,7 kg.(105lb.) excl.handwheel

**MOUNTING DIMENSIONS**

Valve connection : F12/F14/F16/F25/F30  
 MAX. bore :  $\varnothing$ 46 [1.81] or  $\varnothing$ 58 [2.28]  
 Actuator connection : F16/F25  
 MAX. shaft :  $\varnothing$ 55 [2.16] or  $\varnothing$ 78 [3.07]

**TORQUE**

max.OUTPUT : 3050 Nm (26995 lbf.in.)  
 max.INPUT : 160 Nm (1418 lbf.in.)  
 M.A. : 19 ±15%




**rotork gears**

Nijverheidstraat 25  
 7361 LAV, Loosdrecht  
 The Netherlands

**GEARBOX ILG/S 1950 LB**

THIS DOCUMENT IS PROPERTY OF ROTORK GEARS. NEITHER THIS OR ITS CONTENT MAY BE COPIED OR USED IN ANY OTHER WAY DETRIMENTAL TO THE INTEREST OF ROTORK GEARS. ACCEPTANCE OF THIS DOCUMENT SHALL CONSTITUTE ACKNOWLEDGEMENT OF THE FOREGOING CONDITIONS



Drawn : N.M. Date : 05-02-09  
 Dwg Nr.: D34N1LB-001 Rev.: 01

Contents Subject to change without notice.