

DESCRIPTION


TRAVEL : 90° ±5° AT BOTH ENDS.
 RATIO : 211 : 1
 TURNS TO CLOSE : 52.75
 WEIGHT : 45 kg (99.2 lb.) excludhandwheel

MOUNTING DIMENSIONS

Valve connection : F12/F14/F16/F25
 MAX. bore : $\varnothing 46$ [1.81] or $\varnothing 58$ [2.28]
 Actuator connection : F16/F25
 MAX. shaft : $\varnothing 55$ [2.16] or $\varnothing 78$ [3.07]

TORQUE

max.OUTPUT : 6800 Nm (60180 lbf.in.)
 max.INPUT : 103 Nm (912 lbf.in.)
 M.A. : 66 ±15%




Dimensions in MM [inch]

rotork gears

Nijverheidstraat 25
 7561 N, Loosdrecht
 The Netherlands

GEARBOX ILG/S 1950 / SP4

THIS DOCUMENT IS PROPERTY OF ROTORK GEARS. NEITHER THIS OR ITS CONTENT MAY BE COPIED OR USED IN ANY OTHER WAY DETRIMENTAL TO THE INTEREST OF ROTORK GEARS. ACCEPTANCE OF THIS DOCUMENT SHALL CONSTITUTE ACKNOWLEDGEMENT OF THE FOREGOING CONDITIONS



Drawn : J.H

Date : 18-03-02

Dwg Nr.: D35N-001

Rev.: 06

Contents Subject to change without notice.