

DESCRIPTION


TRAVEL : 90° ±5° AT BOTH ENDS.
 RATIO : 211 : 1
 TURNS TO CLOSE : 52.75
 WEIGHT : 57.7 kg.(127 lb.) excludhandwheel

MOUNTING DIMENSIONS

Valve connection: F12/F14/F16/F25/F30
 MAX. bore : $\varnothing 46$ [1.81] or $\varnothing 58$ [2.28]
 Actuator connection : F16/F25
 MAX. shaft : $\varnothing 55$ [2.16] or $\varnothing 78$ [3.07]

TORQUE

max.OUTPUT : 6800 Nm (60180 lbf.in.)
 max.INPUT : 103 Nm (912 lbf.in.)
 M.A. : 66 ±15%




Dimensions in MM [inch]

rotork gears

Nijverheidstraat 25
 7561 LA, Loosdrecht
 The Netherlands

GEARBOX ILG/S 1950/SP4 LB

THIS DOCUMENT IS PROPERTY OF ROTORK GEARS. NEITHER THIS OR ITS CONTENT MAY BE COPIED OR USED IN ANY OTHER WAY DETRIMENTAL TO THE INTEREST OF ROTORK GEARS. ACCEPTANCE OF THIS DOCUMENT SHALL CONSTITUTE ACKNOWLEDGMENT OF THE FOREGOING CONDITIONS



Drawn : N.M. Date : 05-02-09

Dwg Nr.: D35NLAB-001 Rev.: 01

Contents Subject to change without notice.