

**DESCRIPTION**


TRAVEL : 90° ±5° AT BOTH ENDS.  
 RATIO : 325 : 1  
 TURNS TO CLOSE : 81,25  
 WEIGHT : 84 kg.(185 lb.) excl.handwheel

**MOUNTING DIMENSIONS**

Valve connection : F16/F25/F30  
 MAX. bore :  $\varnothing$ 55 [2.17] or  $\varnothing$ 65 [2.56]  
 Actuator connection : F25/F30  
 MAX. shaft :  $\varnothing$ 75 [2.95] or  $\varnothing$ 100 [3.94]

**TORQUE**

max.OUTPUT : 12500 Nm (110630 lbf.in.)  
 max.INPUT : 133.5 Nm (1182 lbf.in.)  
 M.A. : 93,6 ±15%




**rotork gears**

Nijverheidstraat 25  
 7561 LA, Loosdrecht  
 The Netherlands

# GEARBOX ILG/S 6800/SP4

THIS DOCUMENT IS PROPERTY OF ROTORK GEARS. NEITHER THIS OR ITS CONTENT MAY BE COPIED OR USED IN ANY OTHER WAY DETRIMENTAL TO THE INTEREST OF ROTORK GEARS. ACCEPTANCE OF THIS DOCUMENT SHALL CONSTITUTE ACKNOWLEDGEMENT OF THE FOREGOING CONDITIONS



Drawn : J.H  
 Dwg Nr.: D36N-001  
 Date : 18-03-02  
 Rev.: 05

Contents Subject to change without notice.