

DESCRIPTION


TRAVEL : 90° ±5° AT BOTH ENDS.
 RATIO : 325 : 1
 TURNS TO CLOSE : 81,25
 WEIGHT : 114,4kg.(252lb.) excl.handwheel

MOUNTING DIMENSIONS

Valve connection : F16/F25/F30/F35
 MAX. bore : \varnothing 55 [2.17] or \varnothing 65 [2.56]
 Actuator connection : F25/F30
 MAX. shaft : \varnothing 75 [2.95] or \varnothing 100 [3.94]

TORQUE

max.OUTPUT : 12500 Nm (110630 lbf.in.)
 max.INPUT : 133.5 Nm (1182 lbf.in.)
 M.A. : 93,6 ±15%




Dimensions in MM [inch]

rotork gears

Nijverheidsweg 25
 7561 Neth. Loosdrecht
 The Netherlands

GEARBOX ILG/S 6800/SP4 LB

THIS DOCUMENT IS PROPERTY OF ROTORK GEARS. NEITHER THIS OR ITS CONTENT MAY BE COPIED OR USED IN ANY OTHER WAY DETRIMENTAL TO THE INTEREST OF ROTORK GEARS. ACCEPTANCE OF THIS DOCUMENT SHALL CONSTITUTE ACKNOWLEDGEMENT OF THE FOREGOING CONDITIONS



Drawn : N.M.

Date : 05-02-09

Dwg Nr.: D36N1LB-001

Rev.: 01

Contents Subject to change without notice.