


DESCRIPTION
 TRAVEL : 90° ±5° AT BOTH ENDS.
 RATIO : 657 : 1
 TURNS TO CLOSE : 164,25
 WEIGHT : 105 kg.(231lb.) excl.handwheel

MOUNTING DIMENSIONS
 Valve connection : F16/F25/F30
 MAX. bore : \varnothing 55 [2.17] or \varnothing 65 [2.56]
 Actuator connection : F25/F30
 MAX. shaft : \varnothing 75 [2.95] or \varnothing 100 [3.94]

TORQUE
 max.OUTPUT : 17000 Nm (150450 lbf.in.)
 max.INPUT : 92 Nm (814lbf.in.)
 M.A. : 185 ±15%



Dimensions in MM [Inch]

rotork gears
 Nijverheidstraat 25
 7561 PV, Loosdrecht
 The Netherlands

GEARBOX ILG/S 6800/SP9

THIS DOCUMENT IS PROPERTY OF ROTORK GEARS. NEITHER THIS OR ITS CONTENT MAY BE COPIED OR USED IN ANY OTHER WAY DETRIMENTAL TO THE INTEREST OF ROTORK GEARS. ACCEPTANCE OF THIS DOCUMENT SHALL CONSTITUTE ACKNOWLEDGEMENT OF THE FOREGOING CONDITIONS

Drawn : J.B Date : 23-09-02

Dwg Nr.: D36N-002 Rev.: 02

Contents Subject to change without notice.