


DESCRIPTION
 TRAVEL : 90° ±5° AT BOTH ENDS.
 RATIO : 38 : 1
 TURNS TO CLOSE : 9,5
 WEIGHT : 14 kg.(31 lb.) excl.handwheel


MOUNTING DIMENSIONS
 Valve connection : F10/F12/F14/F16
 MAX. bore : \varnothing 32 [1.26] or \varnothing 40 [1.57]
 Actuator connection : F10/F12/F14
 MAX. shaft : \varnothing 36 [1.42] or \varnothing 50 [1.97]

TORQUE
 max.OUTPUT : 1620 Nm (14350 lbf.in.)
 max.INPUT : 123 Nm (1089 lbf.in.)
 M.A. : 13.2 ±15%



rotork gears
 Nijverheidstraat 25
 7561 LA Lisse
 The Netherlands

GEARBOX ILG/S 880
 THIS DOCUMENT IS PROPERTY OF ROTORK GEARS. NEITHER THIS OR ITS CONTENT MAY BE COPIED OR USED IN ANY OTHER WAY DETRIMENTAL TO THE INTEREST OF ROTORK GEARS. ACCEPTANCE OF THIS DOCUMENT SHALL CONSTITUTE ACKNOWLEDGEMENT OF THE FOREGOING CONDITIONS



Drawn : J.H
 Date : 18-03-02
 Dwg N°: D32N-001
 Rev.: 06