





H
G
F
E
D
C
B
A







ISOMETRIC VIEW (SCALE 1:12)

NOTES:
 :DIMENSIONS WITH "*" INDICATE COVER REMOVAL ALLOWANCE
 :ELECTRONICS COVER OPTION "****" WILL VARY DEPENDING ON CONFIGURATION
 :NETT WEIGHT = 94kg/207lbs
 :  = OIL FILLER/DRAIN PLUG
 :THE INTERFACE PROVIDED FOR MOUNTING THE ACTUATOR OR SECOND STAGE GEARBOX ONTO THE VALVE SHOULD CONFORM TO GOOD ENGINEERING PRACTICES, ENSURING ADEQUATELY TOLERANCED LIMITS FOR PARALLELISM, PERPENDICULARITY AND CONCENTRICITY.
 :ROTORK CANNOT BE HELD LIABLE FOR DAMAGE TO OUR EQUIPMENT CAUSED BY EXCESSIVE LOADING FROM COVER TUBES. (SEE ALSO PUB000-124)

CONDUIT ENTRIES



	Hole 1	Hole 2	Hole 3	Hole 4
Size	As Required	As Required	As Required	As Required
Plugged	As Required	As Required	As Required	As Required
Gland	As Required	As Required	As Required	As Required



3D Models are available in various formats under the same drawing number



Actuator Size: IQ10/12/18 IW5,52 & 56RL/MOW5RL		Gearbox output flange options								Maximum Bore & Key			
Title	IQ10/12/18, TOP HANDWHEEL, IW5RL / IW52RL / IW56RL / MOW5RL, F/FA25, Ratios 80 - 288:1 Installation Details	Designation	F25	-	-	-	FA25	-	-	-	Key form	Ø Bore	Key size
Drawn	DH	No. Holes	8	-	-	-	8	-	-	-	Rectangle (BS4235)	76	22 x 14
Checked	NJC	Hole size	M16	-	-	-	5/8" UNC	-	-	-	Rectangle (ANSI B17.1)	3"	3/4 x 1/2"
Date	29-SEP-20	PCD	254	-	-	-	10"	-	-	-	Square (ANSI B17.1)	2-3/4"	5/8" SQ
Ref	SALES	Project Ref QUOTATION											

Issue	Description
1	First Issue

Scale: 1:5

Drawing Number	Issue No	Sheet No
I11THWIW5RLFIL	1	1 of 1

1 2 3 4 5 6 7 8 9 10 11 12