

1	2	3	4	5	6	7	8

## SWITCH CONTACT DIAGRAM

SW	ITCH	CLOSED	- INTERMEDIATE	OPEN
*CTS	4-5			
1013	6-7			
*OTS	8-9			
-013	10-11			
CLS	12-13			
	14-15			
OLS	16-17			
	18-19			
BLK	24-25			

\* CTS & OTS FEEDBACK IS PROVIDED BY CONSIDERING THE TQ. OPERATIONS.

## NOTES:

Е

D

С

В

1. DPDT TORQUEN(CTS, OTS, ACTS, AOTS) AND LIMIT MICROSWITCHES (CLS, OLS, ACLS, AOLS) HAVE 1NO+1NC CONTACTS, ONLY SAME POTENTIAL CAN BE CONNECTED THROUGH BOTH CIRCUITS. STANDARD 250AVC/5A, 24VDC 3A. GOLD CONTACT SWITCHE (LOW ENERG. CIRCUITS) UNDER REQUEST

2. LIMIT SWITCH POSITIONS NO / NC CONTACT SETTABLE BY CAM (ACTUATOR)

3. EXTERNAL POWER SUPPLY FOR HEATER: HEATER MUST BE POWERED ACCORDING TO HEATER RATED VOLTAGE (SEE ACTUATOR ORDER FORM OR ORDER ACKNOWLEDGEMENT), A 250V 50mA QUICK BLOW FUSE MUST BE INSTALLED FOR 120V AND 240V RATED HEATERS

4. CPT ELECTRONIC POSITION TRANSMITTER: VOLTAGE/CURRENT 2, 3 AND 4 WIRES CONFIGURATIONS ARE POSSIBLE. CHECK PROPER TECHNICAL DATASHEET.

5. PRECISION POTENTIOMTER (POT): CHECK OHMIC VALUE

				RSI	ISSUE DESCRIPTION			DATE	ISSUE	ISSUE DESCRIPTION		DATE
				1	1 FIRST PRODUCTION RELEASE 27-			RELEASE 27-06-	22			
				2	2 SWITCH CONTACT DIAGRAM (SHEET 2) ADDED 29			EET 2) ADDED 29-09-	22			
				S	SHEET 2/2 DATE SIGN. WIRING DRAWING			This discl	This drawing and the information it contains are property of Rotork Controls Limited, and they will not be reproduced or disclosed, in whole or in part, without the prior written consent of Rotork.			
				N	ADE BY	27-06-2022	DAB	WD EKQ STD, MSM, 3PH, 2WEP	Τ,	Format	DRAWING N*	
				C	HECKED	27-06-2022	DAB	Noht, LIM+ALS, Tor			504040	
L				A	PPROVED	27-06-2022	NDK				G01010	- Z
	1	2	3	4		5		6		7	8	

Ε

D

С

В

ΙA