

Nijverheidstraat 25 7581 PV Losser PO Box 98 7580 AB Losser – The Netherlands

Mail: <u>info@rotork.com</u> Website: <u>www.rotork.com</u>

AB GEARBOX IP 68-1 CERTIFICATE

| PRODUCT RANGE | AB RANGE |
|------------------|---|
| GEARBOX TYPE | G and W |
| INGRESS | IP 68-1 |
| PROTECTION (IP) | |
| IP - LEVEL 6 | No ingress of dust; complete protection against contact. |
| (DUST TIGHT) | |
| IP – LEVEL 8 – 1 | Gearbox is hermetically sealed, suitable for 72 hours immersion in 1 m |
| (IMMERSION) | head of water. |
| TESTED AGAINST | IEC standard EN 60529 |
| G-TYPE | The G behind the gearbox description indicates that those executions of |
| | the products are sealed to IP 68 and protected accordantly suited for |
| | buried applications. |
| W- TYPE | The W behind the gearbox description indicates that those executions of |
| | the products are sealed to IP 68 - 1 and protected accordantly suited for |
| | water applications. |

CONCLUSION

The assessment on the G and W type was carried out in accordance to IEC standard EN60529 and complied with IP68-1 (immersion in 1m head of water for 72hrs). The IP68-1 enclosure is obtained by adding additional sealing.

Signed

Henk Hoff Engineering Manager

28 November 2013