



Actuator size	Dimension ins/mm						B	C	D	E	F	G
	40	60	spring rating psi		125	150						
250 05	46.8/1189	42.8/1087	41.8/1062	43.8/1113	46.8/1189	47.8/1214	3/8"NPT	5.7/145	11.2/284	18.3/464	.75/19	5.8/146
250 06	43.8/1113	41.8/1062	42.8/1087	44.8/1138	45.8/1163	45.8/1183	3/8"NPT	5.7/145	11.2/284	18.3/464	.75/19	6.8/171
250 07	42.0/1067	42.0/1067	47.0/1194	47.0/1194	49.0/1245	49.0/1245	3/8"NPT	5.9/149	11.2/284	18.5/469	1/25	7.8/197
250 08	44.0/1118	48.0/1219	46.0/1168	48.0/1219	48.0/1219	50.0/1269	1/2"NPT	5.8/146	11.6/294	18.5/469	1/25	8.8/222
250 10	46.3/1176	48.3/1227	48.3/1227	49.3/1252	55.3/1405	55.3/1405	1/2"NPT	5.8/146	11.6/294	18.8/477	1/25	10.8/273
250 12	48.3/1227	48.3/1227	55.3/1405	55.3/1405	---	---	1/2"NPT	5.8/146	11.4/291	18.8/477	1/25	13/330
Actuator size	Weights lbs/kg						Swept Volume US gal/liters					
	40	60	spring rating psi		125	150						
250 05	155/70.3	155/70.3	156/70.8	159/72.1	162/73.5	166/75.4	.40/1.51					
250 06	156/70.8	156/70.8	160/72.5	161/73.0	165/74.8	182/82.7	.58/2.20					
250 07	181/82.1	184/83.4	190/86.1	193/87.5	197/89.3	202/91.6	.79/3.00					
250 08	202/91.6	208/94.3	209/94.8	214/97.0	218/98.8	225/102.0	1.03/3.90					
250 10	231/104.9	237/107.5	242/109.7	248/112.4	260/117.9	265/120.2	1.61/6.12					
250 12	278/126.1	282/127.9	303/137.4	310/140.6	---	---	2.33/8.81					